## **Amendments to the Claims:**

This listing of claims will replace all prior versions and listings of claims in the application:

## **Listing of Claims:**

1. (currently amended): A glass printing ink or glass printing lacquer comprising at least two resins, which together yield a photo-hardenable mixture, and at least one photoinitiator,

wherein one of the at least two resins comprises a bisphenol A based epoxy resin, diluted in a UV hardening monomer, and

another an other of the at least two resins comprises a free functional amino, hydroxy, epoxy, acid, acid anhydride or acrylate groups, wherein the bisphenol A based epoxy resin exhibits a weight average molecular weight in the ränge of substantially 800 to 1500 is selected from the group consisting of: a melamine acrylate; an acid-modified polyester acrylate and an epoxy acrylate.

- 2. (cancelled)
- 3. (cancelled)
- 4. (previously presented): The glass printing ink or glass printing lacquer of claim l, wherein the epoxy resin is used in a quantity of l to 90 wt.% relative to the weight of the glass printing ink or of the glass printing lacquer:
- 5. (previously presented): The glass printing ink or glass printing lacquer of claim l, wherein the other of the at least two resins is used in a quantity of 5 to 90 wt.% relative to the weight of the glass printing ink or of the glass printing lacquer.
- 6. (previously presented): The glass printing ink or glass printing lacquer of claim l, wherein the at least one photoinitiator is present in a total quantity of l to 12 wt.% relative to the weight of the glass printing ink or of the glass printing lacquer.

- 7. (previously presented): The glass printing ink or glass printing lacquer claim 1, wherein the UV hardening monomer is hexanediol diacrylate.
- 8. (previously presented): The glass printing ink or glass printing lacquer of claim l, further comprising a UV hardening reactive diluent other than the UV hardening monomer.
- 9. (previously presented): The glass printing ink or glass printing lacquer of claim 1. further comprising a stabilizer.
- 10. (previously presented): The glass printing ink or glass printing lacquer of claim 1, further comprising a co-initiator.
- 11. (previously presented): The glass printing ink or glass printing lacquer of claim l, further comprising one or more pigments or dyes in a quantity of 0.5 to 50 wt.%, relative to the total weight of the ink.
- 12. 27. (cancelled)
- 28. (new) The glass printing ink or glass printing lacquer of claim l, wherein the bisphenol A based epoxy resin exhibits a weight average molecular weight in the range of substantially 800 to 1500.